
Akira User Manual

Release 1.99.15.20260531075356.32922aefed

Banu Systems Private Limited

May 31, 2026

CONTENTS

1	Installation	3
1.1	Hardware requirements	3
1.2	Supported platforms	3
1.3	RPM platforms	4
1.3.1	Red Hat Enterprise Linux 10 (x86_64)	4
1.3.2	Red Hat Enterprise Linux 10 (aarch64)	5
1.3.3	Red Hat Enterprise Linux 9 (x86_64)	5
1.3.4	Red Hat Enterprise Linux 9 (aarch64)	6
1.3.5	Fedora Linux 44 (x86_64)	6
1.3.6	Fedora Linux 44 (aarch64)	7
1.3.7	Fedora Linux 43 (x86_64)	7
1.3.8	Fedora Linux 43 (aarch64)	8
1.4	Debian and Ubuntu platforms	8
1.4.1	Debian 13 "Trixie" (amd64)	8
1.4.2	Debian 13 "Trixie" (arm64)	9
1.4.3	Debian 13 "Trixie" (riscv64)	9
1.4.4	Debian 12 "Bookworm" (amd64)	10
1.4.5	Debian 12 "Bookworm" (arm64)	11
1.4.6	Ubuntu 26.04 LTS "Resolute Raccoon" (amd64)	11
1.4.7	Ubuntu 26.04 LTS "Resolute Raccoon" (arm64)	12
1.4.8	Ubuntu 26.04 LTS "Resolute Raccoon" (riscv64)	12
1.4.9	Ubuntu 24.04 LTS "Noble Numbat" (amd64)	13
1.4.10	Ubuntu 24.04 LTS "Noble Numbat" (arm64)	14
1.4.11	Ubuntu 24.04 LTS "Noble Numbat" (riscv64)	14
1.4.12	Ubuntu 22.04 LTS "Jammy Jellyfish" (amd64)	15
1.4.13	Ubuntu 22.04 LTS "Jammy Jellyfish" (arm64)	15
1.5	Upgrading	16
2	Programs	17
2.1	akira --- Network management application	17
2.1.1	Synopsis	17
2.1.2	Description	17
2.1.3	Options	17
2.1.4	Files	18
2.1.5	See also	18
2.1.6	Copyright	18

2.2	akira-crypt --- Crypted password generator	19
2.2.1	Synopsis	19
2.2.2	Description	19
2.2.3	Options	19
2.2.4	See also	19
2.2.5	Copyright	19
3	Configuration and data	21
3.1	<code>akira.conf</code> --- akira program's configuration	21
3.1.1	Description	21
3.1.2	Configuration grammar	21
3.1.2.1	<code>akira</code> statement	21
3.1.3	Comments syntax	23
3.1.4	Files	24
3.1.5	See also	24
3.1.6	Copyright	24
4	Release notes	25
4.1	Akira 1.99.15	25
4.2	Border 1.99.14	25
4.3	Border 1.99.13	25
4.4	Border 1.99.12	26
4.5	Border 1.99.11	26
4.6	Border 1.99.10	26
4.7	Border 1.99.9	26
4.8	Border 1.99.8	27
4.9	Border 1.99.7	27
4.10	Version numbering scheme	27
4.10.1	Stable and development versions	28
4.11	Version branches	29
5	License	31
6	Data and privacy	43
	Index	45

Warning

This document is still a work-in-progress. Large parts of it may be inaccurate, and it may mention programs, features and configuration options that do not exist in Akira. This warning will be removed when the manual is known to be correct.

INSTALLATION

1.1 Hardware requirements

Akira is packaged for a set of supported operating system platforms (see [Supported platforms](#)). Any machine (real or virtual) with one of these platforms can be used to run Akira.

For many installations, servers that have been pensioned off from active duty can perform admirably as Akira servers. For serving a small LAN, even low-performance machines may be sufficient. If the server's operational duties are larger, then a suitably performant machine can be selected.

We aren't able to recommend specifications in this document as it would be outdated quickly. It is best to profile the usage patterns and prepare a hardware configuration accordingly.

Error

TODO: Add a link to Akira support for help with hardware configuration.

Error

TODO: Add a link to a tuning section.

1.2 Supported platforms

Akira is written to run on POSIX operating systems. The following platforms are supported by Akira version 1.99.15.20260531075356.32922aefed:

- Red Hat Enterprise Linux 10 (x86_64)
- Red Hat Enterprise Linux 10 (aarch64)
- Red Hat Enterprise Linux 9 (x86_64)
- Red Hat Enterprise Linux 9 (aarch64)

- Fedora Linux 44 (x86_64)
- Fedora Linux 44 (aarch64)
- Fedora Linux 43 (x86_64)
- Fedora Linux 43 (aarch64)
- Debian 13 "Trixie" (amd64)
- Debian 13 "Trixie" (arm64)
- Debian 13 "Trixie" (riscv64)
- Debian 12 "Bookworm" (amd64)
- Debian 12 "Bookworm" (arm64)
- Ubuntu 26.04 LTS "Resolute Raccoon" (amd64)
- Ubuntu 26.04 LTS "Resolute Raccoon" (arm64)
- Ubuntu 26.04 LTS "Resolute Raccoon" (riscv64)
- Ubuntu 24.04 LTS "Noble Numbat" (amd64)
- Ubuntu 24.04 LTS "Noble Numbat" (arm64)
- Ubuntu 24.04 LTS "Noble Numbat" (riscv64)
- Ubuntu 22.04 LTS "Jammy Jellyfish" (amd64)
- Ubuntu 22.04 LTS "Jammy Jellyfish" (arm64)

Packages for current versions of FreeBSD will be added in the future.

Note

For information about Akira's version numbering, see [Version numbering scheme](#). For information about Akira's branches and EOL dates, see [Version branches](#).

1.3 RPM platforms

Note

Users of Red Hat Enterprise Linux clones such as Rocky Linux and AlmaLinux can use the Red Hat Enterprise Linux packages of the corresponding version and follow the corresponding installation instructions.

1.3.1 Red Hat Enterprise Linux 10 (x86_64)

To install Akira version 1.99.15.20260531075356.32922aefed on Red Hat Enterprise Linux 10 (x86_64), follow these steps as the `root` user.

First, install the `akira-release` RPM package that will add the `akira-epel` and `akira-epel-testing` DNF repositories to your system, as well as associated GPG keys used to verify signed RPM packages from these repositories:

```
# dnf install https://download.banuu.com/packages/akira/1.99/
↳ epel/10/x86_64/akira-release-1.99.15.20260531075356.
↳ 32922aefed-1.el10.noarch.rpm
```

Then, install the `akira` RPM package that will install the Akira software and documentation:

```
# dnf install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.3.2 Red Hat Enterprise Linux 10 (aarch64)

To install Akira version 1.99.15.20260531075356.32922aefed on Red Hat Enterprise Linux 10 (aarch64), follow these steps as the `root` user.

First, install the `akira-release` RPM package that will add the `akira-epel` and `akira-epel-testing` DNF repositories to your system, as well as associated GPG keys used to verify signed RPM packages from these repositories:

```
# dnf install https://download.banuu.com/packages/akira/1.99/
↳ epel/10/aarch64/akira-release-1.99.15.20260531075356.
↳ 32922aefed-1.el10.noarch.rpm
```

Then, install the `akira` RPM package that will install the Akira software and documentation:

```
# dnf install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.3.3 Red Hat Enterprise Linux 9 (x86_64)

To install Akira version 1.99.15.20260531075356.32922aefed on Red Hat Enterprise Linux 9 (x86_64), follow these steps as the `root` user.

First, install the `akira-release` RPM package that will add the `akira-epel` and `akira-epel-testing` DNF repositories to your system, as well as associated GPG keys used to verify signed RPM packages from these repositories:

```
# dnf install https://download.banu.com/packages/akira/1.99/
↳ epel/9/x86_64/akira-release-1.99.15.20260531075356.
↳ 32922aefed-1.el9.noarch.rpm
```

Then, install the `akira` RPM package that will install the Akira software and documentation:

```
# dnf install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.3.4 Red Hat Enterprise Linux 9 (aarch64)

To install Akira version 1.99.15.20260531075356.32922aefed on Red Hat Enterprise Linux 9 (aarch64), follow these steps as the `root` user.

First, install the `akira-release` RPM package that will add the `akira-epel` and `akira-epel-testing` DNF repositories to your system, as well as associated GPG keys used to verify signed RPM packages from these repositories:

```
# dnf install https://download.banu.com/packages/akira/1.99/
↳ epel/9/aarch64/akira-release-1.99.15.20260531075356.
↳ 32922aefed-1.el9.noarch.rpm
```

Then, install the `akira` RPM package that will install the Akira software and documentation:

```
# dnf install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.3.5 Fedora Linux 44 (x86_64)

To install Akira version 1.99.15.20260531075356.32922aefed on Fedora Linux 44 (x86_64), follow these steps as the `root` user.

First, install the `akira-release` RPM package that will add the `akira-fedora` and `akira-fedora-testing` DNF repositories to your system, as well as associated GPG keys used to verify signed RPM packages from these repositories:

```
# dnf install https://download.banu.com/packages/akira/1.99/
↳ fedora/44/x86_64/akira-release-1.99.15.20260531075356.
↳ 32922aefed-1.fc44.noarch.rpm
```

Then, install the `akira` RPM package that will install the Akira software and documentation:

```
# dnf install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.3.6 Fedora Linux 44 (aarch64)

To install Akira version 1.99.15.20260531075356.32922aefed on Fedora Linux 44 (aarch64), follow these steps as the `root` user.

First, install the `akira-release` RPM package that will add the `akira-fedora` and `akira-fedora-testing` DNF repositories to your system, as well as associated GPG keys used to verify signed RPM packages from these repositories:

```
# dnf install https://download.banuu.com/packages/akira/1.99/  
↳fedora/44/aarch64/akira-release-1.99.15.20260531075356.  
↳32922aefed-1.fc44.noarch.rpm
```

Then, install the `akira` RPM package that will install the Akira software and documentation:

```
# dnf install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.3.7 Fedora Linux 43 (x86_64)

To install Akira version 1.99.15.20260531075356.32922aefed on Fedora Linux 43 (x86_64), follow these steps as the `root` user.

First, install the `akira-release` RPM package that will add the `akira-fedora` and `akira-fedora-testing` DNF repositories to your system, as well as associated GPG keys used to verify signed RPM packages from these repositories:

```
# dnf install https://download.banuu.com/packages/akira/1.99/  
↳fedora/43/x86_64/akira-release-1.99.15.20260531075356.  
↳32922aefed-1.fc43.noarch.rpm
```

Then, install the `akira` RPM package that will install the Akira software and documentation:

```
# dnf install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.3.8 Fedora Linux 43 (aarch64)

To install Akira version 1.99.15.20260531075356.32922aefed on Fedora Linux 43 (aarch64), follow these steps as the `root` user.

First, install the `akira-release` RPM package that will add the `akira-fedora` and `akira-fedora-testing` DNF repositories to your system, as well as associated GPG keys used to verify signed RPM packages from these repositories:

```
# dnf install https://download.banu.com/packages/akira/1.99/
↳ fedora/43/aarch64/akira-release-1.99.15.20260531075356.
↳ 32922aefed-1.fc43.noarch.rpm
```

Then, install the `akira` RPM package that will install the Akira software and documentation:

```
# dnf install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4 Debian and Ubuntu platforms

1.4.1 Debian 13 "Trixie" (amd64)

To install Akira version 1.99 on Debian 13 "Trixie" (amd64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳ https://download.banu.com/packages/akira/1.99/trixie/13/
↳ amd64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-
↳ keyring.gpg] https://download.banu.com/packages/akira/1.99/
```

(continues on next page)

(continued from previous page)

```
↪debian/trixie/amd64/ "/" > /etc/apt/sources.list.d/akira-  
↪trixie-amd64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.2 Debian 13 "Trixie" (arm64)

To install Akira version 1.99 on Debian 13 "Trixie" (arm64), follow these steps as the root user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg ↪  
↪https://download.banu.com/packages/akira/1.99/trixie/13/  
↪arm64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-  
↪keyring.gpg] https://download.banu.com/packages/akira/1.99/  
↪debian/trixie/arm64/ "/" > /etc/apt/sources.list.d/akira-  
↪trixie-arm64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.3 Debian 13 "Trixie" (riscv64)

To install Akira version 1.99 on Debian 13 "Trixie" (riscv64), follow these steps as the root user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳https://download.banu.com/packages/akira/1.99/trixie/13/
↳riscv64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-
↳keyring.gpg] https://download.banu.com/packages/akira/1.99/
↳debian/trixie/riscv64/ /" > /etc/apt/sources.list.d/akira-
↳trixie-riscv64.list
```

Then, install the akira deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.4 Debian 12 "Bookworm" (amd64)

To install Akira version 1.99 on Debian 12 "Bookworm" (amd64), follow these steps as the root user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳https://download.banu.com/packages/akira/1.99/bookworm/12/
↳amd64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-
↳keyring.gpg] https://download.banu.com/packages/akira/1.99/
↳debian/bookworm/amd64/ /" > /etc/apt/sources.list.d/akira-
↳bookworm-amd64.list
```

Then, install the akira deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.5 Debian 12 "Bookworm" (arm64)

To install Akira version 1.99 on Debian 12 "Bookworm" (arm64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳ https://download.banu.com/packages/akira/1.99/bookworm/12/
↳ arm64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-
↳ keyring.gpg] https://download.banu.com/packages/akira/1.99/
↳ debian/bookworm/arm64/ /" > /etc/apt/sources.list.d/akira-
↳ bookworm-arm64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.6 Ubuntu 26.04 LTS "Resolute Raccoon" (amd64)

To install Akira version 1.99 on Ubuntu 26.04 LTS "Resolute Raccoon" (amd64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳ https://download.banu.com/packages/akira/1.99/resolute/26.
↳ 04 LTS/amd64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-
↳ keyring.gpg] https://download.banu.com/packages/akira/1.99/
↳ ubuntu/resolute/amd64/ /" > /etc/apt/sources.list.d/akira-
↳ resolute-amd64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.7 Ubuntu 26.04 LTS "Resolute Raccoon" (arm64)

To install Akira version 1.99 on Ubuntu 26.04 LTS "Resolute Raccoon" (arm64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳ https://download.banu.com/packages/akira/1.99/resolute/26.
↳ 04 LTS/arm64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-
↳ keyring.gpg] https://download.banu.com/packages/akira/1.99/
↳ ubuntu/resolute/arm64/ /" > /etc/apt/sources.list.d/akira-
↳ resolute-arm64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.8 Ubuntu 26.04 LTS "Resolute Raccoon" (riscv64)

To install Akira version 1.99 on Ubuntu 26.04 LTS "Resolute Raccoon" (riscv64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳ https://download.banu.com/packages/akira/1.99/resolute/26.
↳ 04 LTS/riscv64/akira-archive-keyring-2024-12-10.gpg
```


Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-  
↳keyring.gpg] https://download.banu.com/packages/akira/1.99/  
↳ubuntu/resolute/riscv64/ /" > /etc/apt/sources.list.d/akira-  
↳resolute-riscv64.list
```

Then, install the `akira deb` package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.9 Ubuntu 24.04 LTS "Noble Numbat" (amd64)

To install Akira version 1.99 on Ubuntu 24.04 LTS "Noble Numbat" (amd64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_  
↳https://download.banu.com/packages/akira/1.99/noble/24.04_  
↳LTS/amd64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-  
↳keyring.gpg] https://download.banu.com/packages/akira/1.99/  
↳ubuntu/noble/amd64/ /" > /etc/apt/sources.list.d/akira-  
↳noble-amd64.list
```

Then, install the `akira deb` package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.10 Ubuntu 24.04 LTS "Noble Numbat" (arm64)

To install Akira version 1.99 on Ubuntu 24.04 LTS "Noble Numbat" (arm64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg   
↳ https://download.banu.com/packages/akira/1.99/noble/24.04   
↳ LTS/arm64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-   
↳ keyring.gpg] https://download.banu.com/packages/akira/1.99/   
↳ ubuntu/noble/arm64/ /" > /etc/apt/sources.list.d/akira-   
↳ noble-arm64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.11 Ubuntu 24.04 LTS "Noble Numbat" (riscv64)

To install Akira version 1.99 on Ubuntu 24.04 LTS "Noble Numbat" (riscv64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg   
↳ https://download.banu.com/packages/akira/1.99/noble/24.04   
↳ LTS/riscv64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-   
↳ keyring.gpg] https://download.banu.com/packages/akira/1.99/   
↳ ubuntu/noble/riscv64/ /" > /etc/apt/sources.list.d/akira-   
↳ noble-riscv64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.12 Ubuntu 22.04 LTS "Jammy Jellyfish" (amd64)

To install Akira version 1.99 on Ubuntu 22.04 LTS "Jammy Jellyfish" (amd64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳https://download.banu.com/packages/akira/1.99/jammy/22.04_
↳LTS/amd64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-
↳keyring.gpg] https://download.banu.com/packages/akira/1.99/
↳ubuntu/jammy/amd64/ /" > /etc/apt/sources.list.d/akira-
↳jammy-amd64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.4.13 Ubuntu 22.04 LTS "Jammy Jellyfish" (arm64)

To install Akira version 1.99 on Ubuntu 22.04 LTS "Jammy Jellyfish" (arm64), follow these steps as the `root` user.

First, copy the OpenPGP key that **apt** uses to verify the release's deb package checksums into `/usr/share/keyrings/`:

```
# curl -o /usr/share/keyrings/akira-archive-keyring.gpg_
↳https://download.banu.com/packages/akira/1.99/jammy/22.04_
↳LTS/arm64/akira-archive-keyring-2024-12-10.gpg
```

Then, add the Akira **apt** network package repository for your platform:

```
# echo "deb [signed-by=/usr/share/keyrings/akira-archive-  
↳keyring.gpg] https://download.banu.com/packages/akira/1.99/  
↳ubuntu/jammy/arm64/ /" > /etc/apt/sources.list.d/akira-  
↳jammy-arm64.list
```

Then, install the `akira` deb package that will install the Akira software and documentation:

```
# apt install akira
```

Then, if you wish to run Akira, configure **akira** suitably by editing `/etc/akira/akira.conf`, and then run it:

```
# systemctl enable --now akira
```

1.5 Upgrading

Please read the release notes before upgrading to a newer version of Akira --- see the chapter titled *Release notes*.

PROGRAMS

The following sections document programs that are part of the Akira software distribution.

2.1 **akira** --- Network management application

2.1.1 Synopsis

```
akira [-c <config-file>] [-f] [-g] [-t <directory>] [-u <username>]
```

```
akira [-h | -V]
```

2.1.2 Description

akira is a network management application with a web-based user interface. It also implements a REST API interface that can be used by non-interactive clients.

To access **akira**'s web-based user interface, users require a JavaScript-capable web browser that supports modern web standards.

2.1.3 Options

-c <config-file>

Use <config-file> as the **akira** configuration file. The default is /etc/akira/akira.conf.

-f

Don't daemonize the **akira** process. Run it in the foreground.

-g

Don't daemonize the **akira** process. Run it in the foreground. Force all logging to standard-error.

-h

Print program usage information and exit.

-t <directory>

chroot(2) to <directory> after processing the command line arguments, but before reading the configuration file.

Note

This option should be used in conjunction with the **-u** option, as chrooting a process running as root doesn't enhance security on most systems; the way *chroot*(2) is defined allows a process with root privileges to escape a chroot jail.

-u <username>

setuid(2) to user <username> after completing privileged operations, such as creating sockets that listen on privileged ports.

On Linux, **akira** uses the kernel's capability mechanism to drop all root privileges except the ability to *bind*(2) to a privileged port (`CAP_NET_BIND_SERVICE`) and set process resource limits (`CAP_SYS_RESOURCE`).

-v

Print program version and exit.

2.1.4 Files

`/etc/akira/akira.conf`

The default configuration file. A complete description of **akira**'s configuration file is provided in *akira.conf*(5) and in the Akira User Manual.

`/run/akira/akira.pid`

The default process ID file.

2.1.5 See also

akira.conf(8)

2.1.6 Copyright

Copyright (C) 2025-2026 Banu Systems Private Limited. All rights reserved.

Copyright (c) 2000-2001, 2003-2009, 2011, 2013-2018 Internet Systems Consortium, Inc. ("ISC").

2.2 `akira-crypt` --- Crypted password generator

2.2.1 Synopsis

`akira-crypt`

2.2.2 Description

`akira-crypt` is an interactive command-line program that reads a clear-text password from the user and prints a salted hashed passphrase for use in the `user` statement in *akira.conf(5)*. The hashed passphrase is generated using the *crypt_ra(3)* function with its default setting.

Note

`akira-crypt` needs to be run interactively in a console.

2.2.3 Options

`akira-crypt` does not use any command-line arguments.

2.2.4 See also

akira.conf(5), *crypt_ra(3)*

2.2.5 Copyright

Copyright (C) 2025-2026 Banu Systems Private Limited. All rights reserved.

CONFIGURATION AND DATA

The following sections document configuration files and data files of some programs that are part of the Akira software distribution.

3.1 `akira.conf` --- akira program's configuration

3.1.1 Description

`akira.conf` is the configuration file for *akira*(8) --- a network management application.

3.1.2 Configuration grammar

The configuration file consists of configuration statements and comments. Statements end with a semicolon. Statements and comments are the only elements that can appear without enclosing braces. Many statements contain a block of sub-statements, which are also terminated with a semicolon. Clauses in the statements are also semi-colon terminated. See the [Comments syntax](#) section for a description of comments, and the Akira User Manual for some examples.

`akira.conf` supports the following statements:

akira

Specifies global configuration options.

Note

The `akira` statement may occur only once in the configuration file.

3.1.2.1 `akira` statement

```
akira {  
    enabled <boolean>;  
    jwt-secret <string>;  
    jwt-expiry <ttlval>;  
    listen-on [ port <port:integer> ] { ( <ipv4_address>  
                                          (continues on next page)
```

(continued from previous page)

```
↪| <ipv6_address> ) [ port <integer> ]; ... };
    pid-file ( <quoted_string> | none );
    user <username:quoted_string> <hashed-
↪passphrase:quoted_string>; // may occur multiple times
};
```

The `akira` statement sets up global options to be used by Akira. If there is no `akira` statement, a `akira` statement with each option set to its default value will be used.

Note

The `akira` statement may occur only once in the configuration file.

enabled <boolean>

Warning

This option is obsolete and will be removed in a future release of Akira. Please do not use this option.

jwt-secret <string>

This option specifies a Base64-encoded 64-octet key to be used as the JWT secret. If this option is not specified, a random key is generated in memory by `akira(8)` and used automatically. But the random key is not persistent, and JWT tokens created using such a random key will not be usable after a restart of the `akira(8)` program. For example, after a restart of the `akira(8)` program, this would lead to authentication failures and clients would have to re-authenticate.

jwt-expiry <ttlval>

This option specifies the time in seconds that a JWT token generated by `akira(8)` is valid for. The default value is 1d (1 day).

listen-on [port <port:integer>] { (<ipv4_address> | <ipv6_address>) [...] ;

This option configures the socket addresses on which `akira(8)` listens on. <port> can be specified for all sockets or per-socket as shown in the syntax. The default value is address 127.0.0.1 and port 5009.

pid-file (<quoted_string> | none);

The pathname of the file the **akira** process writes its process ID (PID) to. The default is `/var/run/akira/akira.pid`. The PID file can be used by programs that want to send signals to the **akira** process. Specifying `none` disables the use of a PID file; no file will be written and any existing file will be removed.

Note

`none` is a keyword, not a filename, and therefore must not be enclosed in double quotes.

user <username> <hashed-passphrase>

This option specifies the username and password for a user, using which a user may login into the web interface of *akira*(8). The <username> should be formatted as an email address. <password> should be generated using the *akira-crypt*(1) program.

3.1.3 Comments syntax

The comment syntax allows for comments to appear anywhere that whitespace may appear in a config file. To appeal to all programmers, they can be written in the C, C++, or shell/Perl style:

- C-style comments start with the two characters `/*` (slash, star) and end with `*/` (star, slash). Because they are completely delimited within these characters, they can be used to comment only a portion of a line or to span multiple lines. For example:

```
/*  
 * This is a multi-line  
 * comment.  
 */
```

C-style comments cannot be nested. For example, the following syntax is not valid because the entire comment ends with the first `*/`:

```
/* This is the start of a comment.  
   This is still part of the comment.  
/* This is an incorrect attempt at nesting a comment. */  
   This is no longer in any comment. */
```

- C++-style comments start with the two characters `//` (slash, slash) and continue to the end of the physical line. They cannot be continued across multiple physical lines; to have one logical comment span multiple lines, each line must use the `//` pair. For example:

```
// This is a comment. It continues to end of line.  
// This next line is a new comment, even though it is  
// logically part of the previous comment.
```

- Shell-style or Perl-style comments start with the character `#` (number/hash sign) and continue to the end of the physical line. They cannot be continued across multiple physical lines; to have one logical comment span multiple lines, each line must use the `#` character. For example:

```
# This is a comment. It continues to end of line.  
# This next line is a new comment, even though it is  
# logically part of the previous comment.
```

Note

You cannot use the ";" (semi-colon) character to start a comment such as you would in a zone file. The semicolon indicates the end of a configuration statement.

3.1.4 Files

`/etc/akira/akira.conf`

The configuration file for the *akira(8)* program.

3.1.5 See also

akira(8), *akira-crypt(1)*

3.1.6 Copyright

Copyright (C) 2025-2026 Banu Systems Private Limited. All rights reserved.

Copyright (c) 2004-2018 Internet Systems Consortium, Inc. ("ISC").

RELEASE NOTES

This documentation corresponds to Akira version 1.99.15.20260531075356.32922aefed.

4.1 Akira 1.99.15

The following are release notes for Akira 1.99.15:

- RT1958: Upgrade NPM dependency packages
- RT1951: Add Debian installation instructions to the user manuals
- RT1945: Rename Border to Akira
- RT1948: Add more Bootstrap theme colors
- RT1935: Cleanup border logging shutdown code
- RT1934: Convert printf's in Border into logging messages
- RT1931: Add Ubuntu *Resolute Raccoon* to supported platforms
- RT1929: Fix Debian packaging errors

4.2 Border 1.99.14

The following are release notes for Border 1.99.14:

- RT1923: Upgrade NPM dependency packages
- RT1918: Fix section title syntax error

4.3 Border 1.99.13

The following are release notes for Border 1.99.13:

- RT1911: Upgrade NPM dependency packages
- RT1914: Update code that decrypts Border assets

4.4 Border 1.99.12

The following are release notes for Border 1.99.12:

- RT1891: Fix first release date from 1.99 branch
- RT1879: Upgrade NPM dependency packages
- RT1875: Add missing cocci files to dist
- RT1870: Fix `configure.ac` warnings
- RT1869: Update main copyrights to 2026

4.5 Border 1.99.11

The following are release notes for Border 1.99.11:

- RT1857: Upgrade NPM dependency packages
- RT1837: Upgrade NPM dependency packages
- RT1842: Add libxcrypt to dependencies
- RT1840: Fix release notes text

4.6 Border 1.99.10

The following are release notes for Border 1.99.10:

- RT1819: Fix Debian package homepage URLs

4.7 Border 1.99.9

The following are release notes for Border 1.99.9:

- RT1813: Upgrade NPM dependency packages
- RT1812: Add Debian and Ubuntu to supported platforms
- RT1801: Fix warning about possible thread name buffer overflow (`pthread_setname_np()`)
- RT1799: Upgrade NPM dependency packages
- RT1791: Upgrade NPM dependency packages
- RT1755: Add Debian packaging
- RT1747: Upgrade NPM dependency packages
- RT1746: Fix user creation in RPM spec file for new RPM versions
- RT1743: Disable parallel make in docs directories when using Sphinx
- RT1740: Update list of supported platforms

4.8 Border 1.99.8

The following are release notes for Border 1.99.8:

- RT1674: Reset button in forms clear any previous alerts now.
- RT1679: NPM dependency packages have been upgraded.
- RT1671: libevent and libzip deps are limited to just the border RPM package now.
- RT1681: Installation instructions are now included in the Border User Manual; they were previously missing from the dist.
- RT1682: Form resets are handled more consistently now similar to submit.
- RT1683: Some JavaScript was moved out of the JSX HTML.
- RT1692: NPM dependency packages have been upgraded.
- RT1706: NPM dependency packages have been upgraded.

4.9 Border 1.99.7

This is the first release of Border. Border has been a part of a source code tree with other dependency components such as Loop and Lease for some time now. It was not packaged for release previously.

The following are release notes for Border 1.99.7:

- RT1428: Border is now packaged.
- RT1642: A header was added to Border web licenses.
- RT1664: Border now supports the `listen-on` statement in `border.conf(5)`.
- RT1665: The **border** process now runs as a daemon.
- RT1667: The **border** process now drops privileges when run as `root` user using capabilities under Linux. It also supports being run in a chroot directory.
- RT1666: The **border** process now creates PID files in its runstate directory.
- RT1668: The **border** process is now run as the `border` user when started from the systemd `border.service`.
- RT1673: Copyright year was updated in various web source files.

To install Border, please see the chapter titled [Installation](#).

4.10 Version numbering scheme

Akira version numbers have the grammar `<MAJOR>.<MINOR>.<PATCH>.<COMMIT-TIMESTAMP>.<COMMIT-HASH>`. The *MAJOR* and *MINOR* version numbers together represent a source code branch of Akira (see [Version branches](#)).

- The *MAJOR* version number is incremented when configuration options, API, and behavior of features change compared to the existing version. Switching to a new *MAJOR* version may require modifying existing config files to make them compatible with the new version.
- The *MINOR* version number is incremented when new configuration options, API, and features are introduced that are compatible with existing configuration options. Switching to a new *MINOR* version will not require modifying existing config files to make them compatible with the new version.
- The *PATCH* version number is incremented when only bugs have been fixed in a new version. Switching to a new *PATCH* version will not require modifying existing config files to make them compatible with the new version.
- The *COMMIT-TIMESTAMP* field is auto-generated and contains the UTC timestamp of the source code commit from which the Akira release was made. The timestamp value is formatted as YYYYMMDDHHMMSS, as the output of:

```
date +%Y%m%d%H%M%S
```

- The *COMMIT-HASH* field is auto-generated and contains the abbreviated commit hash of the source code commit from which the Akira release was made. The hash value is formatted as the output of:

```
git log -n1 --reverse --pretty=%h
```

For example,

- If you're upgrading from version 1.2.1 to version 1.4.0, Akira's config files should not require any changes. You may also check for new features that have become available in the 1.4 branch.
- If you're upgrading from version 1.2.1 to version 2.0.0, it is possible that some of the contents of your existing config files may need changes. You may also check for new features that have become available in the 2.0 branch.
- If you're upgrading from version 1.2.1 to version 1.2.4, Akira's config files should not require any changes. The newer version only contains bugfixes.

Note

During a major version's release series, features and/or programs scheduled for removal in the next major release may be marked as deprecated. They will however still be supported until the end-of-life of that major release.

4.10.1 Stable and development versions

Even-numbered *minor* versions indicate stable branch releases, whereas odd-numbered *minor* versions indicate development branch releases. For example,

- 1.2.0 is a stable branch release,

- 1.3.0 is a development branch release,
- 1.99.0 is a development branch release,
- 2.0.3 is a stable branch release, and
- 2.1.1 is a development branch release.

Warning

Development branch releases should not be used in production as their features and interfaces may change. Development branch releases may not work properly, may have unexpected behaviors, may crash, etc.

4.11 Version branches

The following is information on current Akira branches.

Branch	Type	First release date	End-of-life date
1.99	Development	2024-12-10	To be announced
2.0	Stable	To be announced	To be announced

Development branches have no planned end-of-life. Typically, development on such branches is stopped when a new *MINOR*+1 or *MAJOR*+1 stable branch is created off it.

LICENSE

Copyright (C) 2024-2026 Banu Systems Private Limited. All rights reserved.

This product is not open source software. Permission is not granted to redistribute this product.

A proprietary software license is used as an overall license for distributing binaries, documentation, and other works of this product.

THE SOFTWARE IS PROVIDED "AS IS" AND BANU DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL BANU BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions of this product are covered by one or more of the following original copyright and license notices. This product cannot re-license the original unmodified effects and such portions of the product are covered by their original licenses listed below.

Copyright (c) 2004-2018 by Internet Systems Consortium, Inc. ("ISC") Copyright (c) 1995-2003 by Internet Software Consortium

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright (C) 1996-2001 Nominum, Inc. Copyright (C) 2000, 2001, 2004-2015 Nominum, Inc.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND NOMINUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL NOMINUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright (C) 1995-2000 by Network Associates, Inc.

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC AND NETWORK ASSOCIATES DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright (C) 2002 Stichting NLnet, Netherlands, stichting@nlnet.nl.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND STICHTING NLNET DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL STICHTING NLNET BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright (c) 1987, 1990, 1993, 1994 The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (C) The Internet Society 2005. This version of this module is part of RFC 4178; see the RFC itself for full legal notices.

(The above copyright notice is per RFC 3978 5.6 (a), q.v.)

Copyright (c) 2004 Masarykova universita (Masaryk University, Brno, Czech Republic)
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,

BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 1997 - 2003 Kungliga Tekniska Hogskolan (Royal Institute of Technology, Stockholm, Sweden). All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the Institute nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE INSTITUTE AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE INSTITUTE OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 1998 Doug Rabson All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright ((c)) 2002, Rice University All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Rice University (RICE) nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

This software is provided by RICE and the contributors on an "as is" basis, without any representations or warranties of any kind, express or implied including, but not limited to, representations or warranties of non-infringement, merchantability or fitness for a particular purpose. In no event shall RICE or contributors be liable for any direct, indirect, incidental, special, exemplary, or consequential damages (including, but not limited to, procurement of substitute goods or services; loss of use, data, or profits; or business interruption) however caused and on any theory of liability, whether in contract, strict liability, or tort (including negligence or otherwise) arising in any way out of the use of this software, even if advised of the possibility of such damage.

Copyright (c) 1993 by Digital Equipment Corporation.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies, and that the name of Digital Equipment Corporation not be used in advertising or publicity pertaining to distribution of the document or software without specific, written prior permission.

THE SOFTWARE IS PROVIDED "AS IS" AND DIGITAL EQUIPMENT CORP. DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL DIGITAL EQUIPMENT CORPORATION BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright 2000 Aaron D. Gifford. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR(S) AND CONTRIBUTOR(S) ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR(S) OR CONTRIBUTOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 1998 Doug Rabson. Copyright (c) 2001 Jake Burkholder. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (C) 1995, 1996, 1997, and 1998 WIDE Project. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 1999-2000 by Nortel Networks Corporation

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND NORTEL NETWORKS DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT

SHALL NORTEL NETWORKS BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright (c) 2000-2002 Japan Network Information Center. All rights reserved.

By using this file, you agree to the terms and conditions set forth below.

LICENSE TERMS AND CONDITIONS

The following License Terms and Conditions apply, unless a different license is obtained from Japan Network Information Center ("JPNIC"), a Japanese association, Kokusai-Kougyou-Kanda Bldg 6F, 2-3-4 Uchi-Kanda, Chiyoda-ku, Tokyo 101-0047, Japan.

1. Use, Modification and Redistribution (including distribution of any modified or derived work) in source and/or binary forms is permitted under this License Terms and Conditions.
2. Redistribution of source code must retain the copyright notices as they appear in each source code file, this License Terms and Conditions.
3. Redistribution in binary form must reproduce the Copyright Notice, this License Terms and Conditions, in the documentation and/or other materials provided with the distribution. For the purposes of binary distribution the "Copyright Notice" refers to the following language: "Copyright (c) 2000-2002 Japan Network Information Center. All rights reserved."
4. The name of JPNIC may not be used to endorse or promote products derived from this Software without specific prior written approval of JPNIC.
5. Disclaimer/Limitation of Liability: THIS SOFTWARE IS PROVIDED BY JPNIC "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL JPNIC BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Copyright (C) 2004 Nominet, Ltd.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND NOMINET DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions Copyright RSA Security Inc.

License to copy and use this software is granted provided that it is identified as "RSA Security Inc. PKCS #11 Cryptographic Token Interface (Cryptoki)" in all material mentioning or referencing this software.

License is also granted to make and use derivative works provided that such works are identified as "derived from the RSA Security Inc. PKCS #11 Cryptographic Token Interface (Cryptoki)" in all material mentioning or referencing the derived work.

RSA Security Inc. makes no representations concerning either the merchantability of this software or the suitability of this software for any particular purpose. It is provided "as is" without express or implied warranty of any kind.

Copyright (c) 1996, David Mazieres <dm@uun.org> Copyright (c) 2008, Damien Miller <djm@openbsd.org> Copyright (c) 2013, Markus Friedl <markus@openbsd.org> Copyright (c) 2014, Theo de Raadt <deraadt@openbsd.org>

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright (c) 2000-2001 The OpenSSL Project. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
-

3. All advertising materials mentioning features or use of this software must display the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.OpenSSL.org/>)"
4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact licensing@OpenSSL.org.
5. Products derived from this software may not be called "OpenSSL" nor may "OpenSSL" appear in their names without prior written permission of the OpenSSL Project.
6. Redistributions of any form whatsoever must retain the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.OpenSSL.org/>)"

THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 1995, 1997, 1998 The NetBSD Foundation, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,

WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

DATA AND PRIVACY

Akira implements---as part of its software features---support for logging various types of activity for the administrator to use.

- Logging may be performed on behalf of the administrator on the machine where the Akira software is installed.
- Log messages may contain personal data about a user such as, but not limited to, IP addresses, MAC addresses, hostnames, DNS names, TSIG key names, timestamps, etc.

We note that:

- Akira does not share user data or logs with Banu Systems Private Limited, unless the administrator explicitly configures it to do so.
- Akira does not share user data or logs with other companies, organizations, or persons, unless the administrator explicitly configures it to do so.

INDEX

Symbols

-V
 command line option, [18](#)
-c
 command line option, [17](#)
-f
 command line option, [17](#)
-g
 command line option, [17](#)
-h
 command line option, [17](#)
-t
 command line option, [17](#)
-u
 command line option, [18](#)

C

command line option
 -V, [18](#)
 -c, [17](#)
 -f, [17](#)
 -g, [17](#)
 -h, [17](#)
 -t, [17](#)
 -u, [18](#)
enabled, [22](#)
jwt-expiry, [22](#)
jwt-secret, [22](#)
listen-on, [22](#)
pid-file, [22](#)
user, [23](#)

E

enabled
 command line option, [22](#)

J

jwt-expiry

 command line option, [22](#)
jwt-secret
 command line option, [22](#)

L

listen-on
 command line option, [22](#)

P

pid-file
 command line option, [22](#)

U

user
 command line option, [23](#)